10/604,936 uplate

1:15 PM

EAST History		3/15/05	
BRS	1	scalable adj termination	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	27843	impedance adj matching	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	496	S2 and (resistive adj element)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	141	S3 and ports	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	44203	impedance and (termination or terminating or terminate)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	1253	S5 and (resistive adj element)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	367	S6 and ports	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
IS&R	3967	((326/30,86) or (327/108)).CCLS.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	7	S7 and S8	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	17003	impedance and (calibrate or calibrating or calibration)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	606	S10 and (resistive adj element)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS ·	203	S11 and ports	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
BRS	2	S12 and S8	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB